



7301 International Dr.
Holland, OH 43528
(419) 865-5000 phone
(419) 865-1375 fax

Maintenance & Operating Manual					
Sun Shade Products					
Document:			Original Date: 11/8/10		
Revision:			Prepared By: JTS		
Date: 11/8/10			Approved By: MDC		

SUN SHADE STORAGE INSTRUCTIONS

Sun Shades are crated at AWV's factory in an open crate system (unless otherwise specified by customer). All crates upon arrival at the job site, should be covered with a tarp or waterproof cover to assure maximum protection. AWV recommends not to open crating at the job site until the time of installation.

SUN SHADE INSTALLATION

Reference the appropriate approved installation drawing for Sun Shade mounting details and Instructions. Lift Sun Shades into place, use a spreader bar if required. Care must be taken to ensure the Sun Shade frame is not overly racked or twisted. Sun Shades are to be installed per the approved Sun Shade mounting details with respect to blade orientation and sun angle. Sun Shades must be installed square and plumb.

SUN SHADE MAINTENANCE INSTRUCTIONS

Check for and remove any foreign matter that may have accumulated on blades, linkage, screens, or other surfaces, which would cause interference with the movement or resistance of airflow.

SUN SHADE FINISH CLEANING

If you have a painted Sun Shade and the need to clean or remove deposits from the Sun Shade does arise, a variety of methods are available. Two precautions: (1) do not use wire brushes, abrasives, or similar cleaning tools which will mechanically abrade the coating surface, and (2) the use of one of the following cleaning agents listed below should be used on finished surfaces other harsh cleaning agents should be avoided, such as Aromatic and Chlorinated solvents, Keytones, Esters, Lacquer thinner, and Paint remover.

HOT OR COLD DETERGENT SOLUTIONS

A 5% solution in water of commonly used commercial and industrial detergents will not have any deleterious effect on the finished surface. These solutions should be followed by an adequate rinse of water. Use a cloth or soft bristled brush for application.

SOLVENTS

Solvents that may be used to remove non-water soluble deposits (tar, grease, oil, paint, graffiti, etc.) from finished surface.

A. Alcohols

Denature Alcohol (ethanol)

Isopropyl (rubbing alcohol)

Methanol (wood alcohol)

B. Petroleum Solvents and Turpentine

VM & P naptha

Mineral Spirits

Kerosene

Turpentine

WARRANTY

Misuse or abuse of the cleaning agents listed above will result in a voiding of any warranty for the surface affected.